

To get the most from your investment, you need to be able to use your tractor for a multitude of jobs. The TH4335 fits the bill perfectly; it's been designed for maximum comfort and ease of use.

The power steering, ISO mounted operator's platform, ergonomically positioned levers, independent PTO and throttle control (on HST models) make the TH a comfortable tractor that is easy to manoeuvre day after day, year after year. With ROPS as standard and an optional cab available.



Category 1 3-point linkage with 1100 kg lifting capacity

**Power:** 23.86 kW (32 hp)

**Drive System:** Mechanical 12 forward / 12 reverse

**Special Features:** 1100kg lift capacity, power steering,

4 wheel drive & differential lock.

Optional cab available.

## Ransomes Jacobsen Ltd

West Road, Ipswich, IP3 9TT UK Tel: +44 (0) 1473 270000 Web: www.ransomesjacobsen.com





## TH4335 Technical Data

_		
Power	Engine: Type	Diesel, indirect injection, overhead valve
	Displacement	1498cc
	No of cylinders	3
	Power	24.6 kW (32.9 hp) at 2600 rpm
	Fuel capacity	35 ltr (7.7 gal)
Transmission	Type	Mechanical
	Gears forward/reverse	12 /12 with synchro shuttle
	Clutch	Dry single
	Speed	Forward: 0-28 km/h (0-17.4 mph), Reverse: 0-22 km/h (0-13.7 mph)
	Diff lock	Standard
Brakes	Mechanically actuated, sea	led wet disc
Tyres	Front	24 x 8.50-12 (turf); 6-14 (narrow agri); 26 x 12-12 (o/s turf); 7-16 (o/s agri)
	Rear	315/80D-16 (turf); 9.5-22 (narrow agri); 13.6 x 16 (o/s turf); 11.2-24 (o/s agri)
РТО	Engagement	Independent, electro-hydraulic clutch
	Rear PTO at engine rpm	540 PTO rpm @ 2484 rpm / 1000 PTO rpm @ 2291 rpm
	Mid PTO at engine rpm	2080 PTO @ 2600 rpm
Hydraulics	Steering	Hydrostatic (power)
	Main system	Engine mounted gear pump
	Max output at engine rpm	32.1 ltr/min (7.1 gal/min) at 2600rpm
	Three-point lift	Category 1
	Lift capacity	1100kg (2425lbs) at ball ends
	Pump Capacity Sub	13.6 ltr/min (3 gal/min)
	Auxilliary Valves	Standard (x2)
	Joystick Valve	OPT
Dimensions	Overall height with ROPS	2.42m (95.3")
	Overall Length	3.125m (123")
	Overall Width	1.12m (44.09") (1.11m (44.5") across widest ag tyre option), 1.13m (44.49") across narrowest tyre option, 1.43m (56.3") across widest tyre option
	Weight	1268kg (2789lbs)
	Wheelbase	1.69m (66.7")
	Tread Front	880mm (34.5") 1.035m (40.7") O/S turf tyre
	Tread Rear	900mm (35.4") 1.0m (40") 0/S turf tyre
Other Specification	Steering System	Power steering
	Rear Hitch	STD
	ROPS	Rear, folding
	Mower deck	OPT (60 in)





West Road, Ipswich, IP3 9TT UK Tel: +44 (0) 1473 270000 Web: www.ransomesjacobsen.com

