



TM3215/TM3265



Iseki's compact tractor TM series for both private and professional users has been redesigned with versatile features while improving the superior performance. The 3-cylinder engine gives you power to offer better response in difficult field conditions.

The front and rear axles can respond to various field conditions with wet disc brake built in the rear axle. The 4-wheel drive and differential lock ensure solid traction, even on slopes. The simple construction and easy engine access enable you to make the daily maintenance easier. High comfort seat and rubber mounted operator platform make working with the TM range a pleasurable task.



Controls, pedals and levers are placed in optimum position for operator comfort

Power: 3215: 14.5 kW (19.4 hp)
3265: 18.9 kW (25.3 hp)

Drive System: Mechanical or HST

Special Features: Excellent performance coupled with high efficiency. Complete floating mount for reduced noise and vibration.

Ransomes Jacobsen Ltd

West Road, Ipswich, IP3 9TT UK

Tel: +44 (0) 1473 270000

Web: www.ransomesjacobsen.com





TM3215/TM3265 Technical Data

TM3215			
Power	Engine: Diesel, indirect injection, overhead valve		
	Displacement: 1123cc		
	No of cylinders: 3		
	Power: 19.2kw (25hp) at 2500rpm		
	Fuel capacity: 28ltr (7.4 gal)		
Transmission	Hydro	Mech	
	No of speeds:	3	8
	Forward:	1.5-20.1kph (0-12.5mph)	0-21.1kph (0-13mph)
	Driven Wheels:	4WD	4WD
	Differential Lock:	STD	STD
Brakes	Type:	Wet discs	
Tyres	Agri front	6-12	Agri rear 9.5-16
	Turf front	22x8.00-12	Turf rear 31x13.50-15
	Dimensions	Length:	2.8m (110.4")
	Width:	1.1m (43.7")	
	Ground clearance:	0.23m (9.05")	
	Weight HST:	820 kg (1807 lbs)	Mech: 830 kg (1829 lbs)
PTO	Hydro	Mech	
	Shaft:	1 3/8" 6-spline	
	Rear Speed:	550 @ 2500 rpm	545 @ 2500 rpm
	Front Speed:	2047@ 2500 rpm	2032@ 2500 rpm
Hydraulics	Pump Capacity (l/min):	20.1	
	Position control:	Standard	
	Rear Linkage Type:	Category 1	
	Lift Capacity:	600 kg (1322 lbs)	

TM3265			
Power	Engine: Diesel, indirect injection, overhead valve		
	Displacement: 1498cc		
	No of cylinders: 3		
	Power: 25.1kw (33.7hp) at 2500rpm		
	Fuel capacity: 28ltr (7.4 gal)		
Transmission	Hydro	Mech	
	No of speeds:	3	8
	Forward:	1.7-22.2kph (0-13mph)	0-22.2kph (0-13mph)
	Driven Wheels:	4WD	4WD
	Differential Lock:	STD	STD
Brakes	Type:	Wet discs	
Tyres	Agri front	6-12	Agri rear 9.5-18
	Turf front	24x10.50-12	Turf rear 315x75D-15
	Dimensions	Length:	2.87m (112.9")
	Width:	1.1m (43.7")	
	Ground clearance:	0.23m (9.05")	
	Weight HST:	820 kg (1807 lbs)	Mech: 830 kg (1829 lbs)
PTO	Hydro	Mech	
	Shaft:	1 3/8" 6-spline	
	Rear Speed:	567 @ 2600 rpm	571 @ 2600 rpm
	Front Speed:	2032@ 2600 rpm	2129@ 2600 rpm
Hydraulics	Pump Capacity (l/min):	20.1	
	Position control:	Standard	
	Rear Linkage Type:	Category 1	
	Lift Capacity:	600 kg (1322 lbs)	



TM3265 with optional Lewis Loader fitted

Ransomes Jacobsen Ltd

West Road, Ipswich, IP3 9TT UK

Tel: +44 (0) 1473 270000

Web: www.ransomesjacobsen.com

