

EXTRA

787T-787R-787T BX



Triple Mower Conditioners



My way of Farming!

Versatile 8.75m Triple *Mower Conditioners*

High Performance Mowing

The EXTRA 787 series is based on the 700 series platform and includes well-established features like QuattroLink suspension concept, SemiSwing steel tine or rubber roller conditioning and dual adjustment of conditioner plate.

The EXTRA 787 series is developed for maximum productivity and offers excellent ground tracking, easy operation and outstanding versatility.

Comprising two 3.2m mowing units, each with 8 counter-rotating triangular discs, this combination can be operated by tractors starting from 180hp.

EXTRA 787 models are easy to handle and standard operated with a pre-selection joystick for (individual) lifting/lowering of mowing units and belts and setting of ground pressure.

1. QuattroLink® Racecar Suspension

Innovative suspension concept for accurate tracking. The 4-arm suspension provides the mowing unit with an exceptional flexibility in adapting to demanding ground contours.

2. Full Width BreakAway

When encountering an obstacle in the field the mowing unit will swing backwards and over the obstacle, even on the inside of the mower, and then return it to the original mowing position.



“Medium Segment Machine With High End Suspension”



3. Intensive Conditioning

The conditioner plate can be adjusted at both front and rear ends to customize the conditioner to crop intensity. Use the two handles to set the desired conditioning intensity.

4. Vertical Transport Position

Vertical transport position, with a 50/50% weight balance, allows a higher transport speed. With the integrated vertical parking foot limited storage space is required.

5. BX Belt Solution

Vicon BX automatically adjusts belt speed to working width, for the same uniform swath width, regardless of position of mowing units. When sideshifting mowing units during turns etc., this automatic speed adjustment ensures that crop is placed as intended.



The machine folds into a an above 90° transport position, keeping the mowing units away from treetops.



Vicon EXTRA 787 series can be combined with either a 3.2 or 3.6m front.



Vicon EXTRA 787T QuattroLink triple mower combination with 8.75m working width.

Facts

Model EXTRA	Triple Mower Conditioners		
	787T	787R	787T BX
Dimensions & Operation			
Working width (m)	8.75	8.75	8.75
Conditioner	SemiSwing	Roller	SemiSwing
Weight appr. (kg)	2975	3035	3535
Number of triangular discs	2x8	2x8	2x8
PTO power req. min (kW/hp)	130/180	130/180	155/210

Information provided in this brochure is made for general information purposes only and for worldwide circulation. Inaccuracies, errors or omissions may occur and the information may thus not constitute basis for any legal claim against Kverneland Group. Availability of models, specifications and optional equipment may differ from country to country. Please consult your local dealer. Kverneland Group reserves the right at any time to make changes to the design or specifications shown or described, to add or remove features, without any notice or obligations. Safety devices may have been removed from the machines for illustration purposes only, in order to better present functions of the machines. To avoid risk of injury, safety devices must never be removed. If removal of safety devices is necessary, e.g. for maintenance purposes, please contact proper assistance or supervision of a technical assistant. © Kverneland Group Kerttermide AS



vicon.eu



My way of Farming!